

P16045.P01

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

P16045

Total Pages

 Inventor(s) or Application Identifier
 Benzion LANDA, Peretz BEN AVRAHAM, and Becky
 BOSSIDAN

Title: PRINTING ON TRANSPARENT FILM

ADDRESS TO:

 Assistant Commissioner for Patents
 Box Patent Application
 Washington, DC 20231

APPLICATION ELEMENTS

ACCOMPANYING APPLICATION PARTS

1. ☒ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 26]
(preferred arrangement set forth below)
 - Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 USC 113) [Total Sheets 2]
4. ☒ Oath or Declaration [Total Pages 3]
 - a. ☐ Newly executed (original or copy) ☒ Unexecuted
 - b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 18 completed)
[Note Box 5 below]
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s)
named in the prior application, see 37 CFR 1.63(d)(2)
and 1.33(b).
5. ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy
of the oath or declaration is supplied under Box 4b, is considered
as being part of the disclosure of the accompanying application
and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☒ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application,
Status still proper and desired
15. ☒ The prior application is assigned of record to INDIGO N.V.
16. ☒ Foreign priority claimed
 - a. ☒ Claim of Priority
 - b. ☐ Certified Copy of Priority Document(s)
17. ☐ Other: _____

18. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☒ Divisional ☐ Continuation-in-part (CIP) of prior Application No. 08/930,430, filed June 6, 1995.
19. ☐ Amend the specification by inserting before the first line the sentence:This application is a continuation-in-part, continuation, division, of Application No. / , filed .

Address all future correspondence to Customer No. 7055 at the present address of:

 GREENBLUM & BERNSTEIN, P.L.C.
 1941 Roland Clarke Place
 Reston, VA 20191
 (703) 716-1191

Date

Signature

Arnold Turk, Reg No. 33,094

Typed or Printed Name

P16045.A01

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : B. LANDA et al.

Group Art Unit: Unknown

Serial No. : Not Yet Assigned
(Divisional of 08/930,430)

Examiner: Unknown

Filed : Concurrently Herewith

For : PRINTING ON TRANSPARENT FILM

PRELIMINARY AMENDMENT

Commissioner of Patents and Trademarks
Washington, D.C. 20231

Sir:

Prior to examination of the application and calculation of filing fees please enter the following amendment.

IN THE SPECIFICATION

Please amend the specification as follows:

Page 1, after line 1 and immediately following the title, insert the following:

---CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a divisional of Application No. 08/930,430, June 6, 1995, which is the U.S. National Stage of International Application No. PCT/NL95/00193, filed June 6, 1995, and claims priority of Israeli Application No. 113,302, filed April 7, 1995. The entire disclosure of Application No. 08/930,430 is considered as being part of the disclosure of this application, and the entire disclosure of Application No. 08/930,430 is expressly incorporated by reference herein in its entirety.---

Page 1, line 3, delete "an".

08/930,430 "0522E60"

P16045.A01

IN THE CLAIMS

Please cancel claims 1-52 without prejudice or disclaimer of the subject matter contained therein.

Please add claims 53-75, as follows:

---53. A toner particle adapted for use in electrostatic image formation comprising:

a polymer; and

flakes of metal dispersed in the polymer.

54. A toner particle according to claim 53 wherein the flakes of metal have a dimension greater than about 4 micrometers.

55. A toner particle according to claim 54 wherein the flakes of metal have a dimension greater than 6 micrometers.

56. A toner particle according to any of claims 53-55 wherein the metal flakes comprise gold.

57. A toner particle according to any of claims 53-55 wherein the metal flakes comprise silver.

58. A toner particle adapted for use in electrostatic image formation comprising:

a polymer; and

a particulate fluorescent material, dispersed in the polymer.

59. A toner particle according to claim 58 wherein fluorescent material is in the form of particles having a size greater than 2 micrometers.

60. A toner particle according to any of claims 53-55 wherein the polymer is a low molecular weight ionomer.

P16045.A01

61. A toner particle according to claim 56 wherein the polymer is a low molecular weight ionomer.

62. A toner particle according to claim 57 wherein the polymer is a low molecular weight ionomer.

63. A toner particle according to any of claims 58 or 59 wherein the polymer is a low molecular weight ionomer.

64. An electrified toner particle according to any of claims 53-55.

65. An electrified toner particle according to claim 56.

66. An electrified toner particle according to claim 57.

67. An electrified toner particle according to any of claims 58 or 59.

68. A liquid toner comprising:

a plurality of toner particles according to any one of claims 53-55; and
a carrier liquid.

69. A liquid toner comprising:

a plurality of toner particles according to claim 56; and
a carrier liquid.

70. A liquid toner comprising:

a plurality of toner particles according to claim 57; and
a carrier liquid.

P16045.A01

71. A liquid toner comprising:

a plurality of toner particles according to any one of claims 58 or 59; and

a carrier liquid.

72. A printed image printed with a process utilizing a liquid toner according to claim 68.

73. A printed image printed with a process utilizing a liquid toner according to claim 69.

74. A printed image printed with a process utilizing a liquid toner according to claim 70.

75. A printed image printed with a process utilizing a liquid toner according to claim 71.---

REMARKS


Entry of this amendment is respectfully requested prior to examination of the application and calculation of filing fees.

The amendment herein is being presented to include changes to the specification as entered in the parent application, as well as to include the appropriate reference to the parent applications for priority purposes. Additionally, claims are being presented for examination in this divisional application.

P16045.A01

Should the Examiner have any further comments or questions, the Examiner is invited to contact the undersigned at the below-listed telephone number.

Respectfully submitted,
B. LANDA et al.


Arnold Turk
Reg. No. 33,094

May 28, 1999
GREENBLUM & BERNSTEIN, P.L.C.
1941 Roland Clarke Place
Reston, VA 20191
(703) 719-1191

668250"42F22260

1 PRINTING ON TRANSPARENT FILM2 FIELD OF THE INVENTION

3 The present invention relates to an improved
4 electrostatic processes for printing or coating on polymer
5 films and surfaces with toner and toner inks. The invention
6 specifically relates to a method of achieving high quality
7 high contrast colored or multi-colored images in continuous
8 roll printing on transparent, flexible packaging films.

9 BACKGROUND OF THE INVENTION

10 The coating of plastic films or surfaces e.g.
11 polyethylene, polypropylene, etc. for aesthetic or
12 functional purposes is of great utility and importance. A
13 major use of such films is in food packaging.

14 Electrostatic printing has inherent advantages which
15 would appear to make it particularly desirable for printing
16 on plastic films. The inherent advantages include
17 adaptability to short runs economically, high resolution, on
18 demand printing and good visibility. However, at present,
19 printing on transparent films, especially multi-color
20 printing is commercially performed in multi-head presses,
21 and only in long runs.

22 SUMMARY OF THE INVENTION

23 It is an object of certain aspects of the present
24 invention to produce improved quality color images
25 electrostatically on transparent plastic films and
26 substrates.

27 Color integrity of multi-color images is improved by
28 optimizing the image forming and transfer stages of the
29 printing process.

30 In order to improve the visibility of color images
31 printed on the inner surface of transparent flexible
32 packaging, according to a preferred embodiment of the
33 invention, the color image is overcoated with a
34 substantially opaque toner layer at least in those portions
35 of the packaging which are printed with color toners. Thus
36 on the packaging material, at least one color toner layer is

553250" 4242660

5 Alternatively, the complete multi-layer image is
6 printed with the opaque layer uppermost on the intermediate
7 transfer member so that, when the image is transferred to
8 the substrate, the opaque layer is closest to the substrate.
9 Such images are viewed from the printed side of the
10 substrate.

14 In order to avoid unnecessary alignment and
15 registration steps, the different color images involved are
16 sequentially transferred from an image forming surface onto
17 an intermediate transfer member, each in alignment with
18 previous images. The intermediate transfer member is heated
19 so that each color image coalesces into a cohesive film, in
20 which the respective color pigments are held so that they do
21 not diffuse into other layers. Mixing of colors, especially
22 with the opaque pigment is detrimental to image quality.

Another object of certain aspects of the present invention is to provide a process for printing toner polymer images on ionomer (high or low molecular weight) or ethylene vinyl acetate coatings on polymer surfaces, thereby achieving improved qualities. The toner polymer images may be based on high molecular weight ionomers, e.g. Surlyns, low molecular weight ionomers, e.g. Aclyns, ionomers having an intermediate molecular weight, ethylene vinyl acetate polymers and ethelene copolymers or terpolymers e.g., Bynels and Nucrels, to achieve improved qualities, such as sealability, adhesiveness, food compatibility, and others.

In other aspects of the invention special toners, including opaque white, silver, gold and fluorescent toners have been prepared by adding pigments to a hot ionomer solution, preferably of low molecular weight ionomers, and stirring the mixture as it cools. This procedure has been used to prepare gold, silver, white opaque TiO_2 based, magnetic and fluorescent inks, respectively.

There is thus provided, in accordance with a preferred embodiment of the invention, a printing process for forming high contrast color images on polymer surfaces, comprising:

(a) forming a layer of substantially opaque liquid toner comprising polymer based toner particles and a carrier liquid, on an imaging surface;

(b) transferring the layer to an intermediate transfer member;

(c) heating the layer on the intermediate transfer member to a temperature at which the toner particles at least partially coalesce;

(d) repeating (a) to (c) sequentially for at least one subsequent layer in at least one color in image form, said at least one subsequent layer being transferred to the intermediate transfer member onto the opaque layer to form multiple layers on the intermediate transfer member; and

(e) transferring the multiple layers to a polymer surface of a transparent substrate.

There is further provided, in accordance with a preferred embodiment of the invention, a printing process for forming high contrast color images on polymer surfaces, comprising:

(a) forming a colored layer of liquid toner in image form comprising polymer based toner particles and a carrier liquid, on an imaging surface;

(b) transferring the layer to an intermediate transfer member;

(c) heating the layer on the intermediate transfer

H. 1. 07. 00

member to a temperature at which the toner particles at least partially coalesce;

(d) repeating (a) to (c) sequentially for at least a substantially opaque liquid toner layer, said substantially opaque layer being transferred to the intermediate transfer member onto the colored layer to a plurality of layers on the intermediate transfer member; and

(e) transferring the plurality of layers to a polymer surface.

10 Preferably, forming a layer comprises:

(i) charging a photoreceptor surface;

(ii) selectively discharging portions of the charged photoreceptor surface to form a predefined electrostatic image; and

15 (iii) developing a layer of charged opaque white toner particles onto the selectively discharged portions of the photoreceptor surface thereby providing a developed image corresponding to the latent image.

There is further provided, in accordance with a preferred embodiment of the invention, a printing process comprising:

20 a) forming a liquid toner image comprising toner particles based on a first polymer and a carrier liquid, on an imaging surface;

25 (b) transferring the image to a surface coated with a second polymer; and

(c) fusing and fixing the image to the surface coating, wherein the second polymer is either an ionomer or an ethylene vinyl acetate polymer.

30 Preferably, the second polymer is either an ionomer or an ethylene vinyl acetate polymer high molecular weight ionomers, e.g. Surlyns, low molecular weight ionomers, e.g. Aclyns, ionomers having an intermediate molecular weight, ethylene vinyl acetate polymers and ethelene copolymers or
35 terpolymers e.g., Bynels and Nucrels.

There is further provided, in accordance with a

0033474 033359

4.01.07.07

preferred embodiment of the invention, a printing process comprising:

(a) forming a liquid toner image comprising toner particles based on a first polymer and a carrier liquid, on an imaging surface;

(b) transferring the image to a surface coated with a second polymer; and

(c) fusing and fixing the image to the surface coating, wherein the first and second polymer is an ionomer.

Preferably, the first polymer is comprises an ionomer, more preferably the same ionomer as the second polymer.

There is further provided, in accordance with a preferred embodiment of the invention, a toner particle comprising:

a polymer; and
flakes of metal dispersed in the polymer.

Preferably, the flakes which may be of gold or silver, have a dimension greater than about 4 micrometers, more preferably than 6 micrometers.

There is further provided, in accordance with a preferred embodiment of the invention, a toner particle comprising:

a polymer; and
a particulate fluorescent material, preferably in the form of particles having a size greater than 2 micrometers dispersed in the polymer. As used herein the term "particulate fluorescent material" does not include a dyed polymer.

Preferably, the polymer in the above toner particles is a low molecular weight ionomer.

It is, of course, understood that black toner is not suitable for a backing material for a transparent image film since it will result in substantially no image being observed. Thus, to be useful for the present invention should not be made of a completely light absorbing material.

1 BRIEF DESCRIPTION OF THE DRAWINGS

2 The invention will be more clearly understood from the
3 following description of preferred embodiments thereof in
4 conjunction with the following drawings which:

5 Fig. 1 is a simplified sectional illustration of
6 electrostatic imaging apparatus constructed and operative in
7 accordance with a preferred embodiment of the present
8 invention; and

9 Fig. 2 is a simplified enlarged sectional illustration
10 of the apparatus of Fig. 1.

11 DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

12 Reference is now made to Figs. 1 and 2 which illustrate
13 a multi color electrostatic imaging system constructed and
14 operative in accordance with a preferred embodiment of the
15 present invention. As seen in Figs. 1 and 2 there is
16 provided an imaging sheet, preferably an organic
17 photoreceptor 12, typically mounted on a rotating drum 10.
18 Drum 10 is rotated about its axis by a motor or the like
19 (not shown), in the direction of arrow 18, past charging
20 apparatus 14, preferably a corotron, scorotron or roller
21 charger or other suitable charging apparatus as are known in
22 the art and which is adapted to charge the surface of sheet
23 photoreceptor 12. The image to be reproduced is focused by
24 an imager 16 upon the charged surface 12 at least partially
25 discharging the photoconductor in the areas struck by light,
26 thereby forming an electrostatic latent image. Thus, the
27 latent image normally includes image areas at a first
28 electrical potential and background areas at another
29 electrical potential.

30 A preferred photoreceptor sheet and preferred methods
31 of mounting it on drum 10 are described in a co-pending
32 application of Belinkov et al., IMAGING APPARATUS AND
33 PHOTORECEPTOR THEREFOR, filed September 7, 1994 assigned
34 serial number 08/301,775 and in corresponding applications in
35 other countries, the disclosures of which are incorporated
36 herein by reference. Alternatively, photoreceptor 12 may be

66350-12260

1 deposited on the drum 10 and may form a continuous surface.
2 Furthermore, photoreceptor 12 may be a non-organic type
3 photoconductor based, for example, on a compound of
4 selenium.

5 Also associated with drum 10 and photoreceptor sheet
6 12, in a preferred embodiment of the invention, are a
7 multicolor liquid developer spray assembly 20, a developing
8 assembly 22, color specific cleaning blade assemblies 34, a
9 background cleaning station 24, an electrified squeegee 26,
10 a background discharge device 28, an intermediate transfer
11 member 30, cleaning apparatus 32, and, optionally, a
12 neutralizing lamp assembly 36. Developing assembly 22
13 preferably includes a development roller 38. Development
14 roller 38 is preferably spaced from photoreceptor 12
15 thereby forming a gap therebetween of typically 40 to 150
16 micrometers and is charged to an electrical potential
17 intermediate that of the image and background areas of the
18 image. Development roller 38 is thus operative, when
19 maintained at a suitable voltage, to apply an electric field
20 to aid development of the latent electrostatic image.

21 Development roller 38 typically rotates in the same
22 sense as drum 10 as indicated by arrow 40. This rotation
23 provides for the surface of sheet 12 and development roller
24 38 to have opposite velocities at the gap between them.

25 In accordance with a preferred embodiment of the
26 invention, an opaque white background image is initially
27 developed on the photoreceptor surface and transferred to an
28 intermediate transfer member 30. The background image is
29 heated to a temperature that causes the white toner
30 particles in the presence of carrier liquid to at least
31 partially coalesce, preferably into a cohesive film, i.e.,
32 the toner pigment is fixed in the layer in which it was
33 deposited so that mixing of different color pigments in
34 various layers is prevented. This is essential for the
35 achievement of good color quality and contrast in the final
36 composite image. Subsequent images in different colors are

093244-05889

1 individually developed and sequentially transferred in
2 alignment with the previous image onto intermediate transfer
3 member 30, which is heated as before so that each color
4 forms a cohesive non-diffusive layer.

5 It should be noted that each of the layers is a viscous
6 liquid and that while heating does cause the layers to
7 coalesce, the balance between viscosity and surface tension
8 of the layers is apparently such that the individual layers
9 have only minimal mixing.

10 When all of the desired images have been transferred to
11 intermediate transfer member 30, the complete multi-color
12 image is transferred therefrom to substrate 72. Impression
13 roller 71 only produces operative engagement between
14 intermediate transfer member 30 and substrate 72 when
15 transfer of the composite image to substrate 72 takes place,
16 preferably with heat and pressure. Substrate 72 which is
17 preferably a transparent flexible polymer film is fed from a
18 feeder roller 77 and is taken up by take up roller 78. The
19 printing process when carried out as described produces a
20 high contrast high colored quality image.

21 Preferably, the motion of the polymer film is halted
22 during the accumulation of the layers on the intermediate
23 transfer member. Just prior to the transfer, the film is
24 accelerated to a velocity substantially equal to the surface
25 velocity of the intermediate transfer member, such that
26 there is substantially zero relative motion between them at
27 the time of contact. Furthermore, between transfers, the
28 film is preferably partially rewound so that, after the
29 acceleration, only a minimal blank space is left unprinted.

30 Multicolor liquid developer spray assembly 20, whose
31 operation and structure is described in detail in U.S.
32 Patent 5,117,263, the disclosure of which is incorporated
33 herein by reference, may be mounted on axis 42 to allow
34 assembly 20 to be pivoted in such a manner that a spray of
35 liquid toner containing electrically charged pigmented toner
36 particles can be directed either onto a portion of the

093344 093344

1 development roller 38, a portion of the photoreceptor 12
2 or directly into a development region 44 between
3 photoreceptor 12 and development roller 38. Alternatively,
4 assembly 20 may be fixed. Preferably, the spray is directed
5 onto a portion of the development roller 38.

6 Color specific cleaning blade assemblies 34 are
7 operatively associated with developer roller 38 for separate
8 removal of residual amounts of each colored toner remaining
9 thereon after development. Each of blade assemblies 34 is
10 selectably brought into operative association with developer
11 roller 38 only when toner of a color corresponding thereto
12 is supplied to development region 44 by spray assembly 20.
13 The construction and operation of cleaning blade assemblies
14 is described in PCT Publication WO 90/14619 and in US patent
15 5,289,238, the disclosures of which are incorporated herein
16 by reference.

17 Each cleaning blade assembly 34 includes a toner
18 directing member 52 which serves to direct the toner
19 removed by the cleaning blade assemblies 34 from the
20 developer roller 38 to separate collection containers 54,
21 56, 58, 60, and 68 and for each color to prevent
22 contamination of the various developers by mixing of the
23 colors. The toner collected by the collection containers is
24 recycled to a corresponding toner reservoir (55, 57, 59, 61
25 and 63). And a final toner directing member 62 always
26 engages the developer roller 38 and the toner collected
27 thereat is supplied into collection container 64 and
28 thereafter to reservoir 65 via separator 66 which is
29 operative to separate relatively clean carrier liquid from
30 the various colored toner particles. The separator 66 may be
31 typically of the type described in U.S. Patent 4,985,732,
32 the disclosure of which is incorporated herein by reference.

33 In a preferred embodiment of the invention, as
34 described in PCT Publication WO 92/13297, the disclosure of
35 which is incorporated herein by reference, where the imaging
36 speed is very high, a background cleaning station 24

0932244 0339

1 typically including a reverse roller 46 and a wetting roller
2 48 is provided. Reverse roller 46 which rotates in a
3 direction indicated by arrow 50 is preferably electrically
4 biased to a potential intermediate that of the image and
5 background areas of photoconductive drum 10, but different
6 from that of the development roller. Reverse roller 46 is
7 preferably spaced apart from photoreceptor sheet 12 thereby
8 forming a gap therebetween which is typically 40 to 150
9 micrometers.

10 Wetting roller 48 is preferably partly immersed in a
11 fluid bath 47, which preferably contains carrier liquid
12 received from carrier liquid reservoir 65 via conduit 88.
13 Wetting roller 48, which preferably rotates in the same
14 sense as that of drum 10 and reverse roller 46, operates to
15 wet photoreceptor sheet 12 with non-pigmented carrier liquid
16 upstream of reverse roller 46. The liquid supplied by
17 wetting roller 48 replaces the liquid removed from drum 10
18 by development assembly 22, thus allowing the reverse
19 roller 46 to remove charged pigmented toner particles by
20 electrophoresis from the background areas of the latent
21 image. Excess fluid is removed from reverse roller 46 by a
22 liquid directing member 70 which continuously engages
23 reverse roller 46 to collect excess liquid containing toner
24 particles of various colors which is in turn supplied to
25 reservoir 65 via collection container 64 and separator 66.

26 Wetting roller 48 is preferably electrically biased to
27 a potential intermediate that of the image and background
28 areas of photoconductive drum 10, but different from that of
29 the development roller. This biasing of wetting roller 48
30 assists in removing toner particles from the background
31 areas of photoreceptor sheet 12. Wetting roller 48 is
32 preferably spaced apart from photoreceptor sheet 12 thereby
33 forming a gap therebetween which is typically 40 to 200
34 micrometers.

35 The apparatus embodied in reference numerals 46, 47, 48
36 and 70 is generally not required for low speed systems, but

562250 423660

1 is preferably included in high speed systems.

2 Preferably, an electrically biased squeegee roller 26
3 is urged against the surface of sheet 12 and is operative to
4 remove liquid carrier from the background regions and to
5 compact the image and remove liquid carrier therefrom in the
6 image regions. Squeegee roller 26 is preferably formed of
7 resilient slightly conductive polymeric material as is well
8 known in the art, and is preferably charged to a potential
9 of several hundred to a few thousand volts with the same
10 polarity as the polarity of the charge on the toner
11 particles.

12 Discharge device 28 is operative to flood sheet 12 with
13 light which discharges the voltage remaining on sheet 12,
14 mainly to reduce electrical breakdown and improve transfer
15 of the image to intermediate transfer member 30. Operation
16 of such a device in a write black system is described in
17 U.S. Patent 5,280,326, the disclosure of which is
18 incorporated herein by reference.

19 Figs. 1 and 2 further show that multicolor toner spray
20 assembly 20 receives separate supplies of colored toner
21 typically from five different reservoirs 55, 57, 59, 61 and
22 63. Figure 1 shows five different colored toner reservoirs
23 55, 57, 59, 61 and 63, typically containing the colors
24 Yellow, Magenta, Cyan, black and white, respectively. In
25 addition, reservoir 65 contains relatively clean carrier
26 liquid whose operation was described. Pumps 90, 92, 94, 96
27 and 108, may be provided along respective supply conduits
28 98, 101, 103, 105, and 107, for providing a desired amount
29 of pressure to feed the colored toner to multicolor spray
30 assembly 20. Alternatively, multicolor toner spray assembly
31 20, which is preferably a three level spray assembly,
32 receives supplies of colored toner from up to six different
33 reservoirs (a sixth reservoir marked S is shown) which
34 allows for custom colored toners in addition to the standard
35 process colors, black and white.

36 Toners that can be used with the present invention are

668290" 4/2/22E60

1 described in Example 1 of U.S. Patent 4,794,651, the
2 disclosure of which is incorporated herein by reference or
3 variants thereof as are well known in the art. For colored
4 liquid developers, carbon black is replaced by color
5 pigments as is well known in the art. Other toners may
6 alternatively be employed, including liquid toners and, as
7 indicated above, including powder toners.

8 Other toners for use in the invention can be prepared
9 using the following method:

10 1) Solubilizing 1400 grams of Nucrel 925 (ethylene
11 copolymer by Dupont) and 1400 g of Isopar L (Exxon) are
12 thoroughly mixed in an oil heated Ross Double Planetary
13 Mixer at least 24 RPM for 1.5 hours, with the oil
14 temperature at 130° C. 1200 g of preheated Isopar L is added
15 and mixing is continued for an additional hour. The mixture
16 is cooled to 45° C, while stirring is continued over a
17 period of several hours, to form a viscous material.

18 2) Milling and Grinding 762 grams of the result of the
19 Solubilizing step are ground in a 1S attritor (Union Process
20 Inc. Akron Ohio), charged with 3/16" carbon steel balls at
21 250 RPM, together with 66.7 grams of Mogul L carbon black
22 (Cabot), 6.7 grams of BT 583D (blue pigment produced by
23 Cookson), 5 grams of aluminum stearate (Riedel Dehaen) and
24 an additional 1459.6 grams of Isopar L for eight hours at
25 30° C.

26 3) Continuation of Grinding 34.5 grams of ACumist A-12
27 (a micronised polyethylene wax produced by Allied Signal) is
28 added and grinding is continued for an additional 4 hours.
29 The resulting particles are fibrous particles have a
30 measured diameter in the range of 1-3 micrometers.

31 The resulting material is diluted with additional
32 Isopar L and Marcol 82 to give a working developer in which
33 the dry solids portion is about 1.7% and in which the
34 overall ratio of Isopar L to Marcol is between about 50:1
35 and 500:1, more preferably between about 100:1 and 200:1.
36 Charge director as described in US patent application

093390 4422260

1 07/915,291 (utilizing lecithin, BBP and ICIG3300B) and in WO
2 94/02887, in an amount approximately equal to 40 mg/gm of
3 solids in the final dispersion, is added to charge the toner
4 particles. Other charge directors and additional additives
5 as are known in the art may also be used.

6 The above described process produces a black toner.
7 Cyan, magenta and yellow toners can be produced by using a
8 different mix of materials for step 2). For Cyan toner, 822g
9 of the solubilized material, 21.33 grams each of BT 583D and
10 BT 788D pigments (Cookson), 1.73 grams of D1355DD pigment
11 (BASF), 7.59 grams of aluminum stearate and 1426 grams of
12 Isopar L are used in step 2. For Magenta toner, 810 grams of
13 solubilized material, 48.3 grams of Finess Red F2B, 6.81
14 grams of aluminum stearate and 1434.2 grams of Isopar L are
15 used in step 2. For yellow toner 810 grams of solubilized
16 material, 49.1 grams of D1355DD pigment, 6.9 grams of
17 aluminum stearate and 1423 grams of Isopar L are used in
18 step 2.

19 Other preferred liquid toners for use in the present
20 invention are prepared as follows: 300 grams of a
21 chargeable low molecular weight ionomer Aclyn 293A (made by
22 Allied Signal) were solubilized in 1500 grams of Isopar - L
23 with heating to 110°- 120°C while stirring. To form inks,
24 dispersed pigments or color particles are added to and mixed
25 with the hot solubilized polymer. The composition is
26 allowed to cool while stirring.

27 The following liquid toner inks were prepared in this
28 way:

29 **TiO₂ BASED OPAQUE WHITE TONER INK**

30 A preferred opaque white ink in accordance with the
31 present invention is prepared by adding 200 grams of finely
32 divided TiO₂ pigment, having an average diameter of about
33 0.5 micrometers to the solubilized polymer while stirring.
34 The mixture is allowed to cool and settle with continuous
35 stirring. Charge director, as described above or other
36 charged directors as known in the art, and additional Isopar

09324403899

1 L and MARCOL 82 carrier liquid are added to form a liquid
2 toner. The opaque white liquid toner so obtained is used,
3 as previously mentioned, to enhance the quality of color
4 images when it serves as a back layer for color contrast.
5 The median pigmented toner particle size in the toner is
6 4.81 micrometers.

7 An alternative preferred method for producing white
8 toner ink concentrate, in accordance with a preferred
9 embodiment of the invention comprises the steps of (1)
10 plasticizing 35% Nucrel 699 (ethylene-metacrylic acid
11 copolymer by DuPont) in Isopar L (EXXON) by heating the
12 materials in a Ross double planetary mixer to 150°C while
13 mixing the materials and allowing the mixture to cool while
14 mixing continues until the mixture is fully mixed and
15 homogeneous; (2) mixing 3071 grams of the mixture produced
16 by step (1) with 1075 grams of KRONOS 2310 titanium dioxide
17 (NL Chemicals) and 4454 grams of Isopar L in a Ross type LAB
18 ME high shear mixer until the new mixture is completely
19 homogeneous; and (3) grinding the mixture at about 56°C (the
20 temperature of the mixture without cooling) for 16 hours in
21 a SEECO M18 Vibratory Mill charged with 3/8" zirconia media.
22 The resultant toner has a median diameter of about 3
23 microns.

24 The material is charged and diluted as described above
25 and 3 micrometer micron particles of TEFLON M1200 are
26 optionally added to act as protective spacers against
27 abrasion for the final image.

28 Other inks are prepared in a manner similar to the
29 first method for producing white toner ink and provided the
30 following results:

31 **GOLD TONER INK**

32 Aclyn293A, (made by Allied Signal) 150 grams, and
33 Isopar-L, 800 grams, are heated with mixing in a glass
34 beaker, at a temperature of 110° - 120° C. 100 grams of 6-
35 10 micrometer gold flakes (made by SCHLENK) are slowly added
36 and mixing is continued for 5 minutes. The temperature is

093234 05899

1 allowed to fall to 90° C.

2 The composition is mixed at high shear (ROSS HIGH
3 SHEAR MIXER) for 1 minute and cooled, while mixing, to room
4 temperature while mixing is continued at 250 RPM.

5 Final ink median particle size as measured by a
6 SCHIMADZU PARTICLE SIZE ANALYZER is 18.6 micrometers.

7 The ink was tested in an E-PRINT 1000 (using the single
8 final transfer mode described above and separate transfer of
9 individual colors to the final substrates) printer (INDIGO,
10 N.V.) giving metallic gold prints which are free of
11 background contamination. It should be noted that this
12 method of preparing gold ink (and the other inks described
13 below), without grinding, results in large reflective gold
14 particles being laid onto the substrate. While the flakes
15 are unaligned in the toner, when the toner is formed into a
16 thin layer during heating and fixing to the substrate, the
17 flakes selectively align themselves to give good specular
18 reflection.

19 **SILVER INK**

20 The materials used in the preparation are 300 grams
21 Aclyn293A (made by Allied Signal), 1500 grams Isopar-L and
22 100 Grams silver flakes 6-10 micrometers (made by SCHLENK).
23 The same procedure as for gold ink is used to obtain ink
24 with a median particle size of 8.2 micrometers.

25 The ink was tested in both printing modes, in the
26 printer giving metallic silver prints without background
27 contamination.

28 **MAGNETIC INK**

29 The materials used in the preparation are 20 grams
30 Aclyn293A (made by Allied Signal), 37 grams MO 4431 magnetic
31 oxide (made by ISK MAGNETICS) with a particle size of 8-10
32 micrometers and 180 grams Isopar-L. The same procedure as
33 for gold ink is used to obtain magnetic ink with a median
34 particle size of 9.08 micrometers as measured by SCHIMADZU
35 Particle Size Analyzer.

36 When the magnetic ink is deposited at a mass/area of

05334-0539

1 0.26mg./sq.cm., the resultant layer has a magnetic signal
2 of 82% of standard as measured by a NMI apparatus marketed
3 by Checkmate Electronics, and an optical density of 1.5
4 (transmittance).

5 **FLUORESCENT INK**

6 The materials used in the preparation are 500 grams
7 Aclyn293A (made by Allied Signal), 333.3 grams fluorescent
8 pigment RC15 (made by RADIANT COLOR) having a median
9 particle size of 2.5 - 4.5 micrometers and 1500 grams
10 Isopar-L.

11 The resin is solubilized by the ISOPAR L in a ROSS
12 DOUBLE PLANETARY MIXER heated at 110° C.

13 The pigment is predispersed and wetted by using a warm
14 solution of Aclyn293A, then adding the predispersed pigment
15 gradually into the double planetary mixer. The material is
16 mixed for about 10 minutes, while heating is maintained, to
17 obtain a homogeneous composition. Heating is stopped and
18 mixing is continued for an additional 1.5 hours to obtain
19 toner concentrate with a particle size of 3.82 micrometers.
20 Working dispersions are prepared using a high shear mixer.

21 Intermediate transfer member 30 may be any suitable
22 intermediate transfer member having a multilayered transfer
23 portion such as those described below or in US Patents
24 5,089,856 or 5,047,808 or in U.S. Patent application
25 08/371,117, filed January 11, 1995 and entitled IMAGING
26 APPARATUS AND INTERMEDIATE TRANSFER BLANKET THEREFOR (and in
27 corresponding applications in other countries), the
28 disclosures of which are incorporated herein by reference.
29 Member 30 is maintained at a suitable voltage and
30 temperature for electrostatic transfer of the image thereto
31 from the image bearing surface. Intermediate transfer member
32 30 is preferably associated with a pressure roller 71 for
33 transfer of the image onto a final substrate 72, preferably
34 by heat and pressure. Additionally, pressure roller 71 may
35 be electrified to overcome the voltage on the intermediate
36 transfer member or to provide an additional electric field

093244-03339

1 to aid transfer of the electrified toner to the substrate.

2 Cleaning apparatus 32 is operative to scrub clean the
3 surface of photoreceptor 12 and preferably includes a
4 cleaning roller 74, a sprayer 76 to spray a non- polar
5 cleaning liquid to assist in the scrubbing process and a
6 wiper blade 78 to complete the cleaning of the
7 photoconductive surface. Cleaning roller 74, which may be
8 formed of any synthetic resin known in the art, for this
9 purpose is driven in the same sense as drum 10 as indicated
10 by arrow 80, such that the surface of the roller scrubs the
11 surface of the photoreceptor. Any residual charge left on
12 the surface of photoreceptor sheet 12 may be removed by
13 flooding the photoconductive surface with light from
14 optional neutralizing lamp assembly 36, which may not be
15 required in practice.

16 While the invention has been described with respect to
17 printing on the inside of clear wrapping material (i.e.,
18 with the opaque layer furthest from the substrate), in an
19 alternative preferred embodiment of the invention, the layer
20 closest to the substrate is opaque. Such images are designed
21 to be viewed from the side of the substrate on which the
22 image is printed. For this embodiment of the invention, the
23 white layer will be formed on the imaging surface and
24 transferred to the intermediate transfer member after the
25 other, colored layers.

26 In addition to the details of the printing processes
27 given above, additional details of printing processes and
28 operates are given in the patents and publications
29 incorporated herein by reference.

30 It has been found that the above mentioned toners and
31 other toners based on similar materials and high molecular
32 weight ionomers such as surlyns adhere well to the
33 substrates used in food packaging. This adhesion is found to
34 be especially good when the toner is based on an ionomer or
35 ethylene polymer or copolymer and the polymer film is
36 coated by a similar material. Such coatings, particularly

093244 03399

1 Surlyn 1601 ionomer, EVA (particularly low molecular weight
2 EVA) and ethylene acrylic acid are often provided on the
3 inner surface of food wrappings to give improved properties
4 such as sealability, adhesiveness and food compatibility.

5 It should be understood that the invention is not
6 limited to the specific type of image forming system used
7 and the present invention is also useful with any suitable
8 imaging system which forms a liquid toner image on an image
9 forming surface and, the specific details given above for
10 the image forming system are included as part of a best mode
11 of carrying out the invention, however, many aspects of the
12 invention are applicable to a wide range of systems as known
13 in the art for electrostatic printing and copying.

14 It will be appreciated by persons skilled in the art
15 that the present invention is not limited by the description
16 and example provided hereinabove. Rather, the scope of this
17 invention is defined only by the claims which follow:

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

0323174 032399

CLAIMS

- 1
2 1. A printing process for forming high contrast color
3 images on polymer surfaces, comprising:
4 (a) forming a layer of substantially opaque liquid
5 toner comprising polymer based toner particles and a carrier
6 liquid, on an imaging surface;
7 (b) transferring the layer to an intermediate transfer
8 member;
9 (c) heating the layer on the intermediate transfer
10 member to a temperature at which the toner particles at
11 least partially coalesce;
12 (d) repeating (a) to (c) sequentially for at least one
13 subsequent layer in at least one color, said at least one
14 subsequent layer being transferred to the intermediate
15 transfer member onto the opaque layer to form multiple
16 layers on the intermediate transfer member; and
17 (e) transferring the multiple layers to a polymer
18 surface.
19
20 2. A process according to claim 1 wherein the opaque layer
21 is the lowest layer of the multiple layers on the
22 intermediate transfer member.
23
24 3. A printing process for forming high contrast color
25 images on polymer surfaces, comprising:
26 (a) forming a colored layer of liquid toner comprising
27 polymer based toner particles and a carrier liquid, on an
28 imaging surface;
29 (b) transferring the layer to an intermediate transfer
30 member;
31 (c) heating the layer on the intermediate transfer
32 member to a temperature at which the toner particles at
33 least partially coalesce;
34 (d) repeating (a) to (c) sequentially for at least a
35 substantially opaque liquid toner layer, said substantially
36 opaque layer being transferred to the intermediate transfer

093224 052260

1 member onto the colored layer to a plurality of layers on
2 the intermediate transfer member; and

3 (e) transferring the plurality of layers to a polymer
4 surface.

5

6 4. A printing process according to claim 3 and including
7 repeating (a) to (c) sequentially prior to (d) for at
8 least one subsequent layer in at least one different color,
9 said colored and opaque layers forming multiple layers on
10 the intermediate transfer member.

11

12 5. A process according to claim 3 or claim 4 wherein the
13 opaque layer is the uppermost layer of the multiple layers
14 on the intermediate transfer member prior to transfer to the
15 polymer surface.

16

17 6. A process according to any of the preceding claims
18 wherein the colored layers are in the form of an image.

19

20 7. A process according to any of the preceding claims
21 wherein the opaque liquid toner contains a white pigment.

22

23 8. A process according to claim 7 wherein the white
24 pigment is TiO_2 .

25

26 9. A process according to any of the preceding claims
27 wherein forming a layer comprises:

28 (i) charging a chargeable imaging surface;

29 (ii) selectively discharging portions of the charged
30 imaging surface to form a predefined electrostatic image;

31 and

32 (iii) developing a layer of charged opaque white toner
33 particles onto the selectively discharged portions of the
34 imaging surface thereby providing a developed image
35 corresponding to the latent image.

36

003344-03399

4

7

10

13

16

19

22

25

29

33

34 20. A process according to any of the preceding claims in
35 which the toner particle layers form films on the
36 intermediate transfer member.

1

2 21. A printing process comprising:

3 (a) forming a liquid toner image comprising toner
4 particles based on a first polymer and a carrier liquid, on
5 an imaging surface;6 (b) transferring the image to a surface coated with a
7 second polymer; and8 (c) fusing and fixing the image to the surface coating,
9 wherein10 the second polymer is either an ionomer or an ethylene
11 vinyl acetate polymer.

12

13 22. A process according to claim 21 wherein the first
14 polymer is an ionomer.

15

16 23. A process according to claim 22 wherein the first
17 polymer is a high molecular weight ionomer.

18

19 24. A process according to claim 22 wherein the first
20 polymer is a low molecular weight ionomer.

21

22 25. A process according to claim 21 wherein the first
23 polymer is ethylene vinyl acetate.

24

25 26. A process according to claim 21 wherein the polymer is
26 a ethylene copolymer.

27

28 27. A process according to claim 21 wherein the polymer is
29 a ethylene terpolymer.

30

31 28. A process according to any of claims 21-27, wherein
32 the second polymer is an ionomer.

33

34 29. A process according to claim 28, wherein the second
35 polymer is a high molecular weight ionomer.

36

0033440339

3

6

9

12

22

25

28

31

34

35 39. A process according to any of claims 34-38 wherein the
36 surface is a polypropylene film.

2 40. A process according to any of claims 34-38 wherein the
3 surface is a polyethylene film.

5 41. A process according to any of the preceding claims
6 wherein the imaging surface is the surface of a
7 photoreceptor.

9 42. A toner particle comprising:

11 flakes of metal.

13 43. A toner particles according to claim 42 wherein the
14 flakes of metal have a dimension greater than about 4
15 micrometers.

17 44. A toner particle according to claim 43 wherein the
18 flakes of metal have a dimension greater than 6 micrometers.

20 45. A toner particle according to any of claims 42-44
21 wherein the metal flakes comprise gold.

23 46. A toner particle according to any of claims 42-44
24 wherein the metal flakes comprise silver.

26 47. A toner particle comprising:

28 a fluorescent material.

48. A toner particles according to claim 47 wherein
fluorescent material is in the form of particles having a
size greater than 2 micrometers.

34 49. A toner particle according to any of claims 42-48
35 wherein the polymer is a low molecular weight ionomer.

36

1 50. An electrified toner particle according to any of
2 claims 42-49.

3

4 51. A liquid toner comprising:

5 a plurality of toner particles according to any of
6 claims 42-50; and

7 a carrier liquid.

8

9 51. A printed image printed with toner particles according
10 to any of claims 42-50.

11

12 52. A printed image printed with a process utilizing a
13 liquid toner according to claim 51.

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

668250-12122660

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18
- 19
- 20
- 21
- 22
- 23
- 24
- 25
- 26
- 27
- 28
- 29
- 30
- 31
- 32
- 33
- 34
- 35
- 36

Figure 1 consists of 12 bar charts, labeled (a) through (l), each representing a different variable. Each chart compares the percentage of Clinton supporters (n=100) and Clinton opponents (n=100) for that variable. The y-axis for all charts ranges from 0 to 100 percent. The x-axis for each chart lists the categories for the variable.

- (a) Age:** Categories are 18-29, 30-39, 40-49, 50-59, 60-69, 70-79, 80-89, 90-99. Clinton supporters are generally older than opponents.
- (b) Sex:** Categories are Male, Female. Clinton supporters are slightly more female.
- (c) Education:** Categories are Less than high school, High school, Some college, College, Postgraduate. Clinton supporters have higher education levels.
- (d) Income:** Categories are Less than \$10,000, \$10,000-\$19,999, \$20,000-\$29,999, \$30,000-\$39,999, \$40,000-\$49,999, \$50,000-\$59,999, \$60,000-\$69,999, \$70,000-\$79,999, \$80,000-\$89,999, \$90,000-\$99,999, \$100,000 or more. Clinton supporters have higher income levels.
- (e) Employment:** Categories are Not employed, Part-time, Full-time. Clinton supporters are more likely to be full-time employed.
- (f) Home ownership:** Categories are Own, Rent. Clinton supporters are more likely to own their homes.
- (g) Marital status:** Categories are Single, Married, Divorced, Widowed. Clinton supporters are more likely to be married.
- (h) Political affiliation:** Categories are Democrat, Republican, Independent. Clinton supporters are more likely to be Democrats.
- (i) Party identification:** Categories are Democrat, Republican, Independent. Clinton supporters are more likely to identify with the Democratic Party.
- (j) Trust in Clinton:** Categories are No trust, Some trust, A lot of trust. Clinton supporters have more trust in Clinton.
- (k) Confidence in Clinton:** Categories are No confidence, Some confidence, A lot of confidence. Clinton supporters have more confidence in Clinton.
- (l) Confidence in Clinton:** Categories are No confidence, Some confidence, A lot of confidence. Clinton supporters have more confidence in Clinton.

FIG. 1




FIG. 2

Declaration and Power of Attorney For Utility or Design Patent Application

English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

PRINTING ON TRANSPARENT FILM

the specification of which

(check one)

☒ is attached hereto.

☐ was filed on _____ as

Application No. _____

and was amended on _____

(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code §119 (a-d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the "No" box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed:

<u>113,302</u>	<u>ISRAEL</u>	<u>07/April/1995</u>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
_____	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
_____	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No

☐ Additional foreign application numbers are listed on a supplemental priority sheet attached hereto.

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below.

_____	_____
(Number)	(Day/Month/Year Filed)
_____	_____
(Number)	(Day/Month/Year Filed)
_____	_____
(Number)	(Day/Month/Year Filed)

☐ Additional provisional application numbers are listed on a supplemental priority sheet attached hereto.

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s), or §365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

<u>08/930,430</u>	<u>June 6, 1995</u>	<u>pending</u>
(Application No.)	(Filing Date)	(Status)
		(patented, pending, abandoned)
<u>PCT/NL95/00193</u>	<u>June 6, 1995</u>	<u>pending</u>
(Application No.)	(Filing Date)	(Status)
		(patented, pending, abandoned)

☐ Additional U.S. or international application numbers are listed on a supplemental priority sheet attached hereto.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

The undersigned hereby authorizes the U.S. attorney or agent named herein to accept and follow instructions from either his foreign patent agent or corporate representative, if any, as to any action to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorney or agent and the undersigned. In the event of a change in the persons from whom instructions may be taken, the U.S. attorney or agent named herein will be so notified by the undersigned.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the attorney(s) and/or agent(s) associated with the Customer Number provided below to prosecute this application and transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to that Customer Number:

CUSTOMER NUMBER 7055

The appointed attorneys include:

Neil F. Greenblum	Reg. No. 28,394	James L. Rowland	Reg. No. 32,674
Bruce H. Bernstein	Reg. No. 29,027	Roger P. Glass	Reg. No. 30,841
Arnold Turk	Reg. No. 33,094		

At: Greenblum & Bernstein, P.L.C.
1941 Roland Clarke Place
Reston, VA 20191

Direct Telephone Calls to: Greenblum & Bernstein, P.L.C. (703) 716-1191

Full name of sole or first inventor	Benzion LANDA
Inventor's signature	Date
Residence	Nes Ziona, ISRAEL
Citizenship	CANADA
Post Office Address	Kfar Abarron, Nes Ziona, 74051, ISRAEL

(Supply similar information and signature for second and subsequent joint inventors.)

Full name of second joint inventor, if any	Peretz BEN AVRAHAM
Second Inventor's signature	Date
Residence	Rehovot, ISRAEL
Citizenship	ISRAEL
Post Office Address	8 Habosern St.
	Rehovot, ISRAEL
Full name of third joint inventor, if any	Becky BOSSIDAN
Third Inventor's signature	Date
Residence	Rishon Lezion, ISRAEL
Citizenship	ISRAEL
Post Office Address	Usha 6 Kiryat Ganim
	75286 Rishon Lezion, ISRAEL
Full name of fourth joint inventor, if any	
Fourth Inventor's signature	Date
Residence	
Citizenship	
Post Office Address	
Full name of fifth joint inventor, if any	
Fifth Inventor's signature	Date
Residence	
Citizenship	
Post Office Address	
Full name of sixth joint inventor, if any	
Sixth Inventor's signature	Date
Residence	
Citizenship	
Post Office Address	

563230-42722660